



SEE COLOURS IN EVERYTHING



ECOLUX ECOLIGHT Fungus Resistant Emulsion

ECOLIGHT is an economical decorative wall finish suitable for interior and exterior use. **ECOLUX ECOLIGHT** is based on vinyl acetate/acrylate copolymer, which imparts washability and a high degree of durability. It is recommended for use on new walls and when dry, presents a pleasing matt finish with good opacity.

Matt Finish

Ideal For Interior Walls & Ceiling

							
SPRINGFIELD	6014	REBUNG	6016	TULIP	6019	CREAM	6024
							
MERRY WHITE	6025	LIME LIGHT	6022	AMBER WHITE	6020	NATURAL OAK	6033
							
YELLOW PENDANT	6029	CANDLE LIGHT	6023	LINEN	6015	EARTH	6010

Also available in **WHITE 6102** & **BLACK 6103**.

Juga terdapat dalam warna **WHITE 6102** & **BLACK 6103**.
 并备有 **WHITE 6102** & **BLACK 6103**.



SWEETDREAMS

6004



NECTAR

6003



CARNIVAL

6007



PAPRIKA SPRINKLE

6031



MOON SHADOW

6001



PEACH MELODY

6005



SAKURA RED

6027



CANDY

6012



JEANS

6011



OYSTER GREY

6008




ROMANCE

6013



SONIA MAUVE

6030




DEEP SEA

6028



BLUEMOON

6002



BLUE BRUSH

6032



PINANG GREEN

6009

All colours are intermixable. Colours presented are as close as modern printing techniques allow.
 Semua warna boleh dicampur-aduk. Warna yang tertera adalah sehampir mana yang dibenarkan oleh teknik pencetakan moden.
 所有颜色皆可混合。所示色彩是现代印刷技术所能达到的最接近的颜色。

ECOLUX ECOLIGHT

Fungus Resisting Emulsion

ECOLIGHT is a specially formulated decorative wall finish suitable for interior and exterior cement plaster walls, ceilings, asbestos, hard and soft boards, and other cementitious based surfaces. It is durable, easy to apply and when dry, presents a pleasing matt finish that is fungus resistant with good opacity.

SURFACE PREPARATION

Wall surfaces to be painted must be clean, dry and free from loose and flaking materials. Remove fungus and all loose and powdery residues with a wire brush under running water or a high pressure water jet. Areas affected by fungus and algae growth should be treated with **Sissons Anti-Mould Solution**. Apply with one (1) coat of **ECOPRIME** where high alkalinity is present. Do not paint on walls where moisture is high or during wet weather.

THINNING

Thin with 20-25% by volume with water depending upon surface porosity.

APPLICATION

By brush, roller or spray.

DRYING TIME

Approximately 2 hours.

NUMBER OF COATS

2 coats.

COVERAGE

Approximately 11 sq. metres per litre.

CLEANING UP

Clean with water immediately after use.

ECOLIGHT adalah cat penghias berkualiti yang memenuhi keperluan ekonomi. Ia dirumus khas untuk kegunaan dalaman dan luaran bagi permukaan dinding bersimen plaster, bumbung, asbestos, papan keras dan lembut serta pelbagai permukaan bersimen. Ia begitu lasak, mudah digunakan dan memberikan kemas yang menarik dan juga tahan serangan kulat.

PENYEDIAAN PERMUKAAN

Permukaan dinding yang hendak dicat mestilah bersih, kering serta bebas daripada bahan-bahan lejang dan terkupas. Tanggalkan semua kulat serta permukaan berkapur atau rapuh dengan menggunakan berus sabut kasar dan air mengalir atau melalui tekanan jet air. Permukaan yang terjejas dengan kulat dan alga patut dirawat dengan **Sissons Anti-Mould Solution**. Di mana terdapatnya keadaan beralkali tinggi, saluti dengan satu (1) lapisan **ECOPRIME**. Jangan menyapu cat jika kelembapan adalah tinggi atau semasa musim hujan.

PENCAIRAN

Cairkan sebanyak 20-25% dengan air mengikut keporosan permukaan.

PENGGUNAAN

Sesuai untuk penggunaan berus, penggelek atau semburan.

TEMPOH PENGERINGAN

Kira-kira 2 jam.

JUMLAH LAPISAN

2 lapisan.

KADAR LUAS PENGGUNAAN

Kira-kira 11 meter persegi seliter.

PEMBERSIHAN

Bersihkan dengan air serta-merta selepas penggunaan.

ECOLIGHT 是为经济需求而特别配制的高品质墙壁髹饰漆，适合室内及户外水泥抹面墙壁，天花板，石棉，硬木板，软木板及其他水泥基表面等使用。它容易髹饰及持久耐用，在干透后留下悦目的覆盖髹饰效果。

髹饰前表面处理

髹饰表面必须保持清洁，干燥和没有任何松脱或剥落的物体。利用铁丝扫和水流或高压喷水器清除表面的所有真菌松脱和粉状物体。真菌覆盖或长有苔藓的表面须用最新抗霉菌溶液处理。高度碱性的表面须先涂上一层**ECOPRIME**。请勿在高度潮湿的墙壁或潮湿的气候下髹饰。

稀释

混合20-25%的水调稀，视髹饰表面的孔隙程度而定。

应用方法

漆扫，滚筒或喷射。

干透时间

大约2小时。

涂层数量

2层。

覆盖

每公升大约可涂髹11平方公尺。

清理

使用后立刻以清水清洗。



BUATAN MALAYSIA

Sales & Marketing Office:

Level 3A-03A, Menara UAC, 12, Jalan PJU 7/5, Mutiara Damansara, 47800 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: **03-7727 6697 / 03-7726 4009** | Fax: **03-7726 9299**

Ecolux by Boustead Sissons Paints