



SEE COLOURS IN EVERYTHING



ECOLUX ECOMATT PREMIUM Emulsion Paint

Ecomatt is a high quality decorative interior paint specially formulated for high durability and washability with fungus resistance. It is easy to apply and provides excellent coverage with attractive matt finishes.

Low Sheen Finish

Ideal for interior walls and ceiling.

LILY WHITE	5001	APPLE WHITE	5002	ROSE WHITE	5004	ORCHID WHITE	5005
							
BARLEY WHITE	5006	DEBUTANT	5007	CHIFFON	5008	PEACH POWDER	5011
							
MUSKMELON	5016	RATTAN	5018	NATURAL CEDAR	5027	WORN HARNESS	5028

Also available in **WHITE 5102 & BLACK 5103**.
 Juga terdapat dalam warna **WHITE 5102 & BLACK 5103**.
 并备有 **WHITE 5102 & BLACK 5103**.



BARLEY

5017




EGYPTIAN SUN

5022



ORANGE ZEST

5023



BRICK HOUSE

5026



PEBBLE WALK

5039



CURLING BARK

5038



PINK MEADOW

5034



BELLS OF HOLLAND

5041



MOSS PRINT

5035



TEAROSE

5012



JUBILEE

5037



TWILIGHT SKY

5029



LIME FIZZ

5019



ROMANCE

5033



PLUM SPARKLE

5032



LAKE CITY

5031



TROPICANA

5024



FUCHSIA BERRY

5025



ASTORIA

5040



WILD BLUE YONDER

5020

All colours are intermixable. Colours presented are as close as modern printing techniques allow.
Semua warna boleh dicampur-aduk. Warna yang tertera adalah se hampir mana yang dibenarkan oleh teknik pencetakan moden.
所有颜色皆可混合。所示色彩是现代印刷技术所能达至的最接近的颜色。

ECOLUX ECOMATT PREMIUM

Emulsion Paint

ECOMATT PREMIUM is a top quality emulsion paint that dries to give an attractive matt finish and is suitable for all interior and exterior masonry substrates.

SURFACE PREPARATION

Wall surfaces to be painted must be clean and free from loose and flaking materials.

THINNING

ECOMATT PREMIUM is formulated ready for use. For absorbent surfaces, the paint should be thinned 5% by volume with water.

APPLICATION

ECOMATT PREMIUM can be applied by brush, roller or spray.

DRYING TIME

Approximately 2 hours.

NUMBER OF COATS

2 coats.

COVERAGE

Approximately 13.5 sq. metres per litre.

CLEANING UP

Clean with water immediately after use.

ECOMATT PREMIUM adalah cat emulsi bermutu tinggi yang menghasilkan kemasan kusam yang menarik apabila kering dan ianya sesuai untuk permukaan dinding di dalam dan di luar bangunan.

PERSEDIAAN PADA PERMUKAAN

Pastikan permukaan dinding yang akan dicat dalam keadaan bersih, kering dan bebas daripada bahan-bahan lekap dan terkupas.

PENCAIRAN

ECOMATT PREMIUM sedia digunakan. Tapi untuk permukaan yang mudah menyerap cecair, cat perlu dicairkan 5% dengan air.

PENGGUNAAN

ECOMATT PREMIUM boleh digunakan dengan berus, pengelek atau semburan.

TEMPOH PENDINGINAN

Anggaran 2 jam.

JUMLAH LAPISAN

2 lapisan.

KADAR LUAS PENGGUNAAN

Anggaran 13.5 meter persegi seliter.

PEMBERSIHAN

Bersihkan dengan air sebaik sahaja selepas digunakan.

ECOMATT PREMIUM 是一个高品质的乳胶漆，干透后给予室内及室外的石工一层优雅浅淡的光泽。

表面处理

涂髹的墙面必须清洁，干燥并且无松脱和剥落的物质。

稀释

ECOMATT PREMIUM 墙涂可即时应用，根据施工情况，可稀释漆容量 5% 的水。

应用方式

ECOMATT PREMIUM 可以毛刷，滚筒或喷射方式涂髹。

干透时间

大约2小时。

涂髹层数

2层。

用量

每公升大约可涂髹13.5平方公尺。

清洗

使用后需即刻以清水清洗。



Sales & Marketing Office:

Level 3A-03A, Menara UAC, 12, Jalan PJU 7/5, Mutiara Damansara, 47800 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

Tel: 03-7727 6697 / 03-7726 4009 | Fax: 03-7726 9299

Ecolux by Boustead Sissons Paints