



SEE COLOURS IN EVERYTHING



ECOLUX ECOSHIELD Acrylic Paint

ECOLUX ECOSHIELD is designed for exterior use to protect and decorate concrete fasciae, cement plaster or rendering and other cement based surfaces. It is fungus resistant with excellent weathering properties and is specially formulated for tropical weather. For maximum protection, at least two coats should be applied.

Acrylic Paint


Ideal for outdoor.



CORNER CUPBOARD 1010



HOPEFUL BLUE 1016



MINERALE 1029



PLANKTON 1020



GARDEN GREEN 1027




TANZANIA 1028



CITRUS LIME 1001



MYTHOLOGY 1005



TRACKING TAN 1026



OREGANO 1031



WEATHERBURN TAN 1023



NEUTRAL 1032

Also available in **WHITE 1103 & BLACK 1102**.
 Juga terdapat dalam warna **WHITE 1103 & BLACK 1102**.
 并备有 **WHITE 1103 & BLACK 1102**.



All colours are intermixable. Colours presented are as close as modern printing techniques allow.
 Semua warna boleh dicampur-aduk. Warna yang tertera adalah se hampir mana yang dibenarkan oleh teknik pencetakan moden.
 所有颜色皆可混合。所示色彩是现代印刷技术所能达至的最接近的颜色。

ECOLUX ECOSHIELD

Acrylic Paint

ECOSHIELD is an extremely durable coating for protection and decoration of all exterior masonry surfaces. It is extremely resistant to fungus growth and attack from alkali. Its special acrylic binder also ensures excellent adhesion of paint to the substrate.

SURFACE PREPARATION

Wall surfaces to be painted must be clean and dry. Remove all loose materials with a stiff fibre brush under running water or a high pressure water jet. **ECOSHIELD** is a self priming finish. Where high alkalinity is present, apply 1 coat of **ECOPRIME**.

THINNING

The paint is ready for use but for absorbent surface, it should be thinned between 5-10% by volume with water to assist application of the first coat. On subsequent coats, no thinning is required for application by brush. 5% thinning is sufficient to assist roller application under normal circumstances.

APPLICATION

Suitable for applications by brush, roller or spray.

DRYING TIME

Approximately 2 hours.

NUMBER OF COATS

2 coats.

COVERAGE

Approximately 11 sq. metres per litre.

CLEANING UP

Clean with water immediately after use.

ECOSHIELD adalah cat yang mampu bertahan lama untuk perlindungan dan mengindahkan semua bahagian permukaan berbatu luar. Ia tahan serangan kulat dan alkali. Pengikat akrilik juga memastikan pelekatan cat yang sempurna.

PERSEDIAAN PADA PERMUKAAN

Permukaan dinding yang hendak dicat mestilah bersih dan kering. Buangkan bahan-bahan yang mengelupas dengan berus sabut yang keras berserta dengan air atau dengan tekanan air yang tinggi. Cat **ECOSHIELD** memberikan kemasan yang tersendiri. Di mana terdapatnya keadaan beralkali tinggi, sapukan satu (1) lapisan **ECOPRIME** terlebih dahulu.

PENCAIRAN

Cat sedia digunakan tapi bagi permukaan yang mudah menyerap cecair, cat perlu dicairkan 5-10% dengan air bagi memudahkan kerja-kerja mengecat lapisan pertama. Pada lapisan seterusnya, cat tidak perlu dicairkan jika proses mengecat menggunakan berus. 5% pencairan adalah memadai bagi memudahkan kerja mengecat menggunakan pengelek ke atas permukaan berkeadaan biasa.

PENGUNAAN

Sesuai untuk penggunaan berus, pengelek atau semburan.

TEMPOH PENGERINGAN

Anggaran 2 jam.

JUMLAH LAPISAN

2 lapisan.

KADAR LUAS PENGGUNAAN

Anggaran 11 meter persegi seliter.

PEMBERSIHAN

Bersihkan dengan air sebaik sahaja selepas digunakan.

ECOSHIELD 是一种超强耐久的涂层，可有效保护及修饰室外的砖石屋瓦等表面。它拥有高度排除真菌类植物的生长以及碱性的侵蚀。它独特的丙烯酸结合剂也可确保漆料可以牢固地紧贴着底层。

表面处理

要涂髹的墙画必须清洁及干净。用流水和坚硬的纤维刷或高压水枪除去所有的松脱物质。**ECOSHIELD**本身就是基涂。如果是高碱性的地方，可先涂髹一层时新防碱 **ECOPRIME** 的基涂。

稀释

此涂料已调配好，可即可应用，但如果是吸收力强的表层，必须在第一次涂髹时先以漆量 5- 10% 的清水稀释。接下来涂髹若使用毛刷就无需再稀释，若使用滚筒则在一般的情况下需以5%清水稀释。

应用方法

适宜使用毛刷，滚筒或喷射方式。

干透时间

大约2小时。

涂髹层数

2层。

用量

每公升大约可涂髹11平方公尺。

清洗

使用后需即刻以清水清洗。



Sales & Marketing Office:

Level 3A-03A, Menara UAC, 12, Jalan PJU 7/5, Mutiara Damansara, 47800 Petaling Jaya, Selangor Darul Ehsan, Malaysia.
Tel: 03-7727 6697 / 03-7726 4009 | Fax: 03-7726 9299

Ecolux by Bostead Sissons Paints