



# Sissons

## SISCOSEAL DECORATIVE WOOD STAIN



Wood Preservative,  
Weather Resistant



Will Not Crack,  
Peel or Blister



No Added  
Lead & Mercury



# Sissons

## SISCOSEAL

### DECORATIVE WOOD STAIN

Unveil The Splendor of Wood Stain - Bring out the natural lustre of timber. See it come to life in sheer brilliance, time after time.



Golden Pine **SS103**



Rust **SS105**




Teak **SS104**




Redwood **SS107**




Mahogany **SS102**



Rosewood **SS108**




Beech **SS106**



Meranti **SS101**



Juniper **SS109**



Charcoal **SS110**

Siscoseal Decorative Wood Stain is based on a special resin and contains preservatives for the decoration and protection of all timber surfaces against rot and mould growth. It is water resistant and will not crack, peel or blister on exposure to the weather.

**Surface Preparation:** Ensure the surface is clean, dry and free from paint or varnish prior to application. No primer or undercoat is required.

**Application:** The paint is ready for use and should not be thinned. It is suitable for application by brush.

**Drying Time:** Allow for overnight drying between coats.

**Number Of Coats:** 2 coats.

**Coverage:** Approximately 14 sq metres per litre.

**Cleaning Up:** Clean with mineral turpentine or white spirit.

Siscoseal Pewarna Hiasan Kayu berasaskan damar khas dan mengandungi bahan awet untuk mengindahkan dan melindungi permukaan kayu daripada reput dan menghindari pertumbuhan kulat. Ia kalis air dan tidak mudah retak, mengelupas atau bergelembung akibat kesan cuaca.

**Persediaan Pada Permukaan:** Pastikan permukaan yang hendak dicat bersih, kering dan bebas dari kesan varnis. Tidak perlu menggunakan cat asas.

**Penggunaan:** Cat sedia digunakan terus dan tidak perlu pencairan. Sesuai digunakan dengan berus.

**Tempoh Pengerian:** Biarkan kering semalaman selepas setiap lapisan.

**Jumlah Lapisan:** 2 lapisan.

**Kadar Luas Penggunaan:** Anggaran 14 meter persegi seliter.

**Pembersihan:** Bersihkan dengan turpentine atau spirit.

丝高髹木料装饰剂配自一种特别的树脂，并含有防腐剂以确保一切新质表层获得适当的装饰与保护，免受腐蚀以及霉菌的破坏。它可以防水而且暴露在恶劣天气下也不会破裂、剥落或起水疱。

**表层处理:** 必须确保涂髹前的表层清洁、干燥并且无漆。无需使用底漆或防锈涂层。

**应用方法:** 丝高髹可即时应用，适宜使用毛刷涂髹，但不可稀释。

**干透时间:** 须隔天方可重复涂髹。

**涂髹层数:** 2层。

**用量:** 每公升大约可涂髹14平方公尺。

**清洗:** 可使用矿物松节油或白火酒清洗。



All colours are intermixable. Colours presented are as close as modern printing techniques allow. Semua warna boleh dicampur-aduk. Warna yang tertera adalah sehampir mana yang dibenarkan oleh teknik pencetakan moden. 所有颜色皆可混合。所示色彩是现代印刷技术所能达至的最接近的颜色。